


WAFER LED | SURFACE MOUNT

58710 / 58711 / 58810 / 58712 / 58713 / 58812 / 57714 / 58715 / 58814 / 58736 / 58737 / 58780 / 58784

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____

- Power Source is Patent Pending
- 120 - 277 Input
- Aluminum Construction
- Polycarbonate Lens
- Size Options: 5.5", 7", 9," and 15"
- Thin 0.5" profile from surface
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Finish Options: White (WT) Black (BK) Bronze (BZ) and Satin Nickel (SN)
- Dimmable Options: ELV at 120V and 0-10V
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge Lit LED Technology creates bright and even illumination
- Suitable for Wet Locations above showers and covered ceilings outdoor
- cETLus
- JA8 Title 24 and Energy Star 2.0 Listed



58780WT
7" Empty Shell




58784WTWT
Wafer LED 7" RD w/ 1.5 hours
Emergency Back Up



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



Installs into 3-0 or 4-0 junction box with a minimum of 1.5" depth

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)
- Black (BK)



MATERIAL:

Aluminum Construction
Polycarbonate Lens

AVAILABLE SIZES:

5.5" | 7" | 9" | 15"

RATINGS:

cETLus
Wet Location
Energy Star
Title 24 JA8 compliant
ADA
Dimmable:
Closets Rated: 410.8 & 410.16



ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40°C (104°F)
PHOTOMETRIC: Report Found Online

MODEL	DIMENSION	BULB TYPE	CRI	LUMENS INIT DEL	COL TEMP.	DIMMABLE	INPUT
58710	5.5"D x 0.5"H	10W PCB LED (Integrated)	90	930 750	3000K	ELV at 120V	120V -277
58711	5.5"D x 0.5"H	10W PCB LED (Integrated)	90	930 750	3000K	0 - 10V	120V -277
58810	5.5"D x 0.5"H	10W PCB LED (Integrated)	90	930 750	4000K	ELV at 120V	120V -277
58712	7"D x 0.5"H	15W PCB LED (Integrated)	90	1350 1100	3000K	ELV at 120V	120V -277
58713	7"D x 0.5"H	15W PCB LED (Integrated)	90	1500 1200	3000K	0 - 10V	120V -277
58812	7"D x 0.5"H	15W PCB LED (Integrated)	90	1500 1250	4000K	ELV at 120V	120V -277
57714	9"D x 0.5"H	20W PCB LED (Integrated)	90	2100 1700	3000K	ELV at 120V	120V -277
58715	9"D x 0.5"H	20W PCB LED (Integrated)	90	2250 1800	3000K	0 - 10V	120V -277
58814	9"D x 0.5"H	20W PCB LED (Integrated)	90	2200 1800	4000K	ELV at 120V	120V -277
58736	15"D x 0.5"H	30W PCB LED (Integrated)	90	3000 2400	3000K	ELV at 120V	120V -277
58737	15"D x 0.5"H	30W PCB LED (Integrated)	90	3000 2400	4000K	ELV at 120V	120V -277
58780	7"D x 1.25"H						
58784	7"D x 1.75"H	17W PCB LED (Integrated)	90	1250 1000	3000K	0 - 10V	120V -277

Always consult a qualified electrician before installing any lighting product